



PERFORMANCE SPECIFICATIONS

MODEL NUMBER: 350-740-C3*
 WG SIZE: WRD350
 FREQ: 3.50 - 8.20 GHz
 MAX. VSWR: 1.10 MAX.
 RF POWER: 550 WATTS

*C3 IS STANDARD FLANGE. FOR DIFFERENT FLANGE, SUBSTITUTE "C3" WITH CORRESPONDING CODE FOR DESIRED FLANGE AS SHOWN ON TABLE BELOW.

*FLANGE TYPE		
C1	COVER	ALT. THRU/TAPPED
C2	COVER	ALL TAPPED
C3	COVER	ALL THROUGH
G1	GROOVE	ALT. THRU/TAPPED
G2	GROOVE	ALL TAPPED
G3	GROOVE	ALL THROUGH

THIRD ANGLE PROJECTION:		APPROVALS	DATE	ADVANCED TECHNICAL MATERIALS, INC. TEL: (631) 289-0363 FAX: (631) 289-0358 www.atmmicrowave.com		<small>THE INFORMATION IN THIS DRAWING IS PROPRIETARY AND SHALL NOT BE USED OR DISCLOSED WITHOUT THE PRIOR WRITTEN CONSENT OF ATM, INC. DO NOT SCALE DWG.</small>	
UNLESS OTHERWISE NOTED, DIMENSIONS ARE IN INCHES. TOLERANCES ARE: FRACTIONS: ±1/64 ANGLES: ±1/2° MACHINED FINISH 63 ✓ OR BETTER		DRAWN M.R.	8/10/11			WRD 350 MED. POWER TERM.	
		CHKD.		CAGE CODE OR8N4	ATM DWG # 12184		
		APRVD.		MATERIAL ALUM.	SCALE 1 : 1	MODEL # 350-740-XX	SHEET 1/1
DECIMALS 2 PLACE 3 PLACE ±.01 ±.005		TREATMENT CHEM FILM					
		FINISH ATM STD GRAY					