

REVISIONS							
REV	DESCRIPTION	DATE	APPROVED				
Α	INITIAL RELEASE	11/8/00					
В	DELETED CORNER RELIEF AT FIN OPENINGS	9/20/02					
С	MODEL NO. 750-745-XX WAS 750-750-XX	3/25/03					
D	UPDATED DRAWING FORMAT	12/22/04					
Е	FORMAT, NOTES UPDATED.	1/27/05					





## PERFORMANCE SPECIFICATIONS

MODEL NUMBER: 750-745-FLANGE TYPE\* WAVEGUIDE SIZE: WRD750

7.5 – 18.0 GHz 1.10 MAX FREQUENCY RANGE:

VSWR: RF POWER: 700 WATTS

*FLANGE TYPE						
C1	COVER	ALT. THRU/TAPPED				
C2	COVER	ALL TAPPED				
C3	COVER	ALL THROUGH				
G1	GROOVE	ALT. THRU/TAPPED				
G2	GROOVE	ALL TAPPED				
G3	GROOVE	ALL THROUGH				

MATERIAL ALUM.	TREATMENT IF	RIDITE	DRAWN	R.T.	KESNER	DATE 11	/17/99
FINISH HI-TEMP BLACK	MOD NO. 7	50-745-XX	CHECKED			DATE	
OUTLINE, TERMINATION,	WRD7	50 POWER	APPROVED	1		DATE	
121(101114)(11014;		OWER	CAGE COD	E: OR	BN4	DO NOT	SCALE DWG
ADVANCED TECHNICAL MATERI 49 RIDER AVE., PATCHOGUE N TEL: (631) 289–0363 FAX: (63 http://www.atmmicrowo	.Y. 11772 1) 289-0358 ave.com	UNLESS OTHERW NOTED DIMENSIO ARE IN INCHES TOLERANCES AR	NS FRACII	54	ECIMALS ±.03 ±.005	ANGLES ±1/2°	1/1
THE INFORMA IS PROPRIETA BE USED OR	TION IN THIS DRAWING RY AND SHALL NOT DISCLOSED WITHOUT RITTEN CONSENT OF		NONE	DWO NO.	41	29	E E