



*NOTE: SECONDARY TERMINATION CAN BE INTERNAL OR EXTERNAL DEPENDING ON MODEL AND SHOULD NOT BE REMOVED. FOR CONNECTORIZED LOADS CONSULT FACTORY.

APPLICATION TABLE	
MODEL#	COUPLING VALUE
C119Ka-10	10dB
C119Ka-20	20dB
C119Ka-30	30dB

THIRD ANGLE PROJECTION:		APPROVALS	DATE			L-3 Narda - ATM TEL: (631) 289-0363 FAX: (631) 289-0358 www.atmmicrowave.com		THE INFORMATION IN THIS DRAWING IS PROPRIETARY AND SHALL NOT BE USED OR DISCLOSED WITHOUT THE PRIOR WRITTEN CONSENT OF AT&M, INC. DO NOT SCALE DWG.	
UNLESS OTHERWISE NOTED, DIMENSIONS ARE IN INCHES, TOLERANCES ARE: FRACTIONS: ±1/64 ANGLES: ±1/2° MACHINED FINISH 63 ✓ OR BETTER		DRAWN M.R.	03/29/17	OUTLINE DIRECTIONAL COUPLER		SIZE A CAGE CODE OR8N4 ATM DWG # 18619 REVISION A			
DECIMALS 2 PLACE 3 PLACE		CHKD.							
±.01 ±.005		APRVD.		MATERIAL ALUM BODY		SCALE 1 : 1		MODEL # SEE TABLE SHEET 1/1	
		TREATMENT -		CHEM FILM					